

# **Standard Cabinets**

## **DESCRIPTION**

Our **Sframe<sup>™</sup> Standard Cabinets** are engineered for quick assembly and immediate use in your data center operations, with specifications designed to accommodate installation of any standard rack-mounted networking equipment















## **SPECIFICATIONS**

- 19-inch mounting width suitable for most networking equipment Conforms to
- industry standard ANSI/EIA-310-D and IEC 60297-3 mounting configuration 1000kg (2205lbs) static load capacity
- Body and frame fabricated from cold rolled steel
- Matte black powder-coated finish
- Front Vertical Cable Management with covers (for 800mm Wide Racks only)

## **DOOR OPTIONS**

Sframe<sup>™</sup> Standard Cabinets are offered with an option of four types of door options:



perforation mesh door D (default front for 800mm wide range)



perforation barn door F (default rear for 800mm wide range)



smokey-gray glass door B (default front for 600mm wide range)



steel casement door A (default rear for 600mm wide range)

Sframe™ images, data, and content © 2015, 2016 . All rights reserved.







Standard Cabinets 18U, 27U, 37U, 42U, 45U, 47U

1200mm (47.24") 800mm (31.50")

## CABINET CONFIGURATIONS

NO.	ITEM	QTY	UNIT	MATERIAL	SURFACE FINISH	REMARKS	
1_	Top cover	1	PC	1.2mm cold-rolled steel	Powder coating	4 removable cable passing pedestal included	
2	Frame	2	PC	1.2mm cold-rolled steel	Powder coating		
3	Front door	1	PC	1.2mm perforation steel		and a	
4	Side panel	2	PC	1.2mm cold-rolled steel	Powder coating	With lock latch	
5	Rear door	1	PC	1.2mm split perforation steel	Powder coating		
6	Lock	2	PC	J-1-1	<del></del>		
7	Mounting rail	4	PC	2.0mm cold-rolled steel	Powder coating		
8	Mounting angle	6	PC	1.5mm cold-rolled steel	Powder coating		
9	Bottom plate	1	PC	1.2mm cold-rolled steel	Powder coating	4 removable cable passing pedestal included	
10	Vertical C/M	2	PC	1.2mm cold-rolled steel	Powder coating	Only for 800mm wide racks	
11	Fan & Thermostat	1	PC			Optional part and to be ordered separately	
12	Caster Front/Rear	4	PC			2x with brake & 2x without	
13	Supporting foot	4	PC	<u> </u>	200		
14	M6 screw and nut	40	set	Luca:	pcose:	20 sets for 18U/27U	

## **CONFIGURATIONS**

Standard Cabinets are offered in the following standard configurations - stock only available by order for SKU marked with "\*"

RACK UNITS	CABINET HEIGHT	CABINET WIDTH	CABINET DEPTH	PART NUMBER	DOOR	COLOR
18U	988mm (38.90 inches)	600mm (23.62 inches)	600mm(23.62 inches)	SCB-PKST-DB-18U66	glass door)	CBK (black) CWH (white) (Optional)
			800mm(31.50 inches)	SCB-PKST-DB-18U68		
2711	4200 (54.65 : 1 )		600mm(23.62 inches)	SCB-PKST-DB-27U66		
27U	1388mm (54.65 inches)		800mm(31.50 inches)	SCB-PKST-DB-27U68		
			1000mm(39.37 inches)	SCB-PKST-DB-27U610		
37U(by order)	1833mm (72.16 inches)		800mm(31.50 inches)	SCB-PKST-DB-37U68 *		
1	=	600mm (23.62 inches)	600mm(23.62 inches)	SCB-PKST-DB-42U66		
	2055mm (80.91 inches)		800mm(31.50 inches)	SCB-PKST-DB-42U68		
			1000mm(39.37 inches)	SCB-PKST-DB-42U610		
42U			1200mm(47.24 inches)	SCB-PKST-DB-42U612 *		
		800mm (31.50 inches)	800mm(31.50 inches)	SCB-PKST-DB-42U88		
			1000mm(39.37 inches)	SCB-PKST-DB-42U810		
			1200mm(47.24 inches)	SCB-PKST-DB-42U812 *		
	2150mm (84.65 inches)	600mm (23.62 inches)	600mm(23.62 inches)	SCB-PKST-DB-45U66		
			800mm(31.50 inches)	SCB-PKST-DB-45U68		
			1000mm(39.37 inches)	SCB-PKST-DB-45U610		
45U			1200mm(47.24 inches)	SCB-PKST-DB-45U612 *		
		800mm (31.50 inches)	800mm(31.50 inches)	SCB-PKST-DB-45U88		
			1000mm(39.37 inches)	SCB-PKST-DB-45U810		
			1200mm(47.24 inches)	SCB-PKST-DB-45U812 *		
1		600mm (23.62 inches)	600mm(23.62 inches)	SCB-PKST-DB-47U66 *		
			800mm(31.50 inches)	SCB-PKST-DB-47U68 *	]	
47U			1000mm(39.37 inches)	SCB-PKST-DB-47U610 *		
	2278mm (89.69 inches)		1200mm(47.24 inches)	SCB-PKST-DB-47U612 *		
(by order)	ELYGIIIII (65.65 illelies)	800mm (31.50 inches)	800mm(31.50 inches)	SCB-PKST-DB-47U88 *		
			1000mm(39.37 inches)	SCB-PKST-DB-47U810 *		
			1200mm(47.24 inches)	SCB-PKST-DB-47U812 *		

- Standard configurations can be ordered as <PART NUMBER>-<COLOR> (eg. SCB-PKST-DB-42U88-DF-CBK)
- Custom configurations also available upon request, please contact our Sales team for more information



